



**MASSEY FERGUSON**

# MF FL/900X

Hard working, high performance loaders




# Specifications

## MF FL Professional Series Loaders

	Diagram reference	New Zealand <sup>^</sup>								
		FL 4018	FL 4121	FL 4323	FL 4626	FL 5033	FL 3723	FL 4125	FL 4227	
Maximum lift height at pivot pin* (m)		4.02	4.06	4.25	4.6	4.96	3.79	4.06	4.25	
Maximum lift height under level bucket* (m)	6	3.72	3.76	3.95	4.3	4.66	3.49	3.76	3.95	
Clearance with bucket dumped 45 degrees* (m)		3.05	3.09	3.28	3.63	3.99	2.82	3.09	3.28	
Lift capacity to maximum height @ 800mm from pivot pin** (kg)	1	1,780	1,980	2,140	2,170	2,590	1,290	1,300	1,590	
Lift capacity to 1.5m height @ 800mm from pivot pin** (kg)		1,820	2,100	2,350	2,460	2,810	1,720	1,870	2,110	
Breakout force @ 800mm from pivot pin** (kg)	2	1,910	2,290	2,470	2,620	3,630	1,850	2,070	2,270	
Roll-back force at ground level @ 800mm from pivot pin** (kg)	3	3,400	3,370	3,400	3,970	4,510	3,420	3,420	4,030	
Maximum dump angle at maximum height (degrees)	5	54	57	57	54	53	58	56	57	
Maximum roll-back angle at ground level (degrees)	4	49	48	48	49	47	48	48	48	
Lifting rams diameter (mm)		75/40	80/40	85/50	90/50	95/50	80/40	85/50	90/50	
Tilting rams diameter (mm)		85/40	85/40	85/40	90/40	100/50	85/40	85/40	90/40	
Weight – standard configuration (kg)		580	620	720	760	830	515	560	630	

<sup>^</sup> Non self-levelling

### Loader Function Diagram



1 Lifting force at pivot pin

2 Lifting force 800 mm from pivot pin

3 Max. roll-back force 800 mm from pivot pin

4 Maximum roll-back angle at ground level

5 Maximum dump angle at maximum height

6 Maximum lift height under level bucket

# Specifications

## MF 900 X Utility Series Loaders

	Diagram reference	MF 916 X	MF 926 X	MF 936 X	MF 946 X	MF 956 X
Maximum lift height – at pivot pin* (m)		2.9	3.10	3.40	3.70	3.90
Maximum lift height – under level bucket* (m)	6	2.7	2.90	3.20	3.50	3.70
Lift capacity to maximum height at pivot pin** (kg)		1,170	1,240	1,410	1,510	1,600
Lift capacity to ground level at pivot pin** (kg)	1	-	1,950	2,100	2,320	2,520
Lift capacity to maximum height @ 800 mm from pivot pin** (kg)		960	1,220	1,520	1,590	1,680
Lift capacity to 1.5m height @ 800 mm from pivot pin** (kg)		1,170	1,400	1,560	1,710	1,890
Lift capacity to ground level @ 800 mm from pivot pin** (kg)	2	-	1,580	1,660	1,850	2,080
Roll-back force at ground level @ 800 mm**	3	1,400	1,500	1,890	2,280	2,740
Maximum dump angle at maximum height (degrees)	5	47	50	50	49	46
Maximum roll-back angle at ground level (degrees)	4	46	42	44	42	43
Lifting rams diameter (mm)		55	60	65	70	75
Tilting rams diameter (mm)		65/40	65/40	70/40	75/40	80/40
Weight – standard configuration (kg)		340	360	390	420	440

\* Height values for standard tractor (depends on tyres and equipments)  
 \*\* lifting force at 195 bar/2,828 PSI  
 – Not applicable

# Specifications

## Tractor/Loader Recommendations

### MF 900 FL Professional Series Loaders

	FL 4018	FL 4121	FL 4323	FL 4626	FL 5033
MF 5600	•	•			
MF 5700	•				
MF 5700 SL	•	•			
MF 6700 S		•	•		
MF 7614/15			•	•	
MF 7714/15/16/18			•	•	
MF 7720/22/24/26				•	•
MF 8700					•

New Zealand <sup>^</sup>		
FL 3723	FL 4125	FL 4227
•	•	
•		
•	•	
	•	•
		•
		•

<sup>^</sup> Non self-levelling

### MF 900 X Utility Series Loaders

Models	MF 916 X	MF 926 X	MF 936 X	MF 946 X	MF 956 X
MF 2600	•	–	–	–	–
MF 4608	–	•	–	–	–
MF 4609/10	–	–	•	–	–
MF 4707/08	–	–	•	–	–
MF 400	–	–	–	•	–
MF 5700	–	–	–	•	–

• Available  
– Not applicable



facebook.com/MasseyFergusonGlobal  
twitter.com/AGCOcorp  
youtube.com/MasseyFergusonVideo  
blog: agcocorp.com

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.



MASSEY FERGUSON is a worldwide brand of AGCO.



**MASSEY FERGUSON**