

LINER side swathers <sup>1</sup>		1750	1700	1650 TWIN	1600 TWIN	1600	800 TWIN	700 TWIN	500 PROFIL	450	420	370	500 T	450 T
<b>Dual-rotor swathers</b>							<b>Single-rotor swathers</b>							
Mounting							Swinging drawbar / hitch	Swinging drawbar / hitch	Three-point	Three-point / swivel-ling head	Three-point / swivel-ling head	Three-point / swivel-ling head	Swinging drawbar / hitch	Swinging drawbar / hitch
Hitch category		Cat. II	Cat. II	Cat. II	Cat. II	Cat. II	–	–	Cat. II	Cat. I + II	Cat. I + II	Cat. I + II	–	–
Working width	m (DIN)	8.00	6.60	6.80–7.90	6.20–6.90	6.20	4.00–7.50	3.50–6.30	4.80	4.50	4.20	3.70	4.80	4.50
Transport width														
With tine arms mounted	m	2.96	2.89/2.99	2.88	2.89/2.99	2.89/2.99	3.60	3.00	3.80 <sup>3</sup>	3.50 <sup>3</sup>	3.20 <sup>3</sup>	2.98 <sup>3</sup>	3.80 <sup>3</sup>	3.50 <sup>3</sup>
With tine arms removed	m	–	–	–	–	–	2.42	2.42	2.40	2.30	2.00	1.53 <sup>4</sup> / 1.75	2.50	2.20
Transport height														
With tine arms mounted	m	3.99	3.99	3.99	3.64	3.79	–	–	–	–	–	–	–	–
With tine arms removed	m	3.69	3.67	3.55	–	–	–	–	2.45	2.45	2.35	2.15	2.45	2.45
Parking length (transport position)	m	9.54	8.66	8.60	8.25	8.25	8.55	8.00	3.30	4.10	3.80	2.55	4.40	5.25
Weight approx.	kg	2625	2080	2230	1950	1810	1620	1440	805	670	650	470	785	715
Rotors	Qty	2	2	2	2	2	2	2	1	1	1	1	1	1
Rotor diameter	m	3.80	3.20	3.20	2.90	2.90	3.50	2.90	3.80	3.50	3.20	2.90	3.80	3.50
Tine arms per rotor	Qty	14	12	12	11	11	12	11	14	12	12	11	14	12
Dual tines per arm set	Qty	4	4	4	4	4	4	4	4	4	4	3 (4 ○)	4	4
Tine diameter	mm	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.00	9.00	9.00	9.50	9.00
PROFIX tine arm bracket		●	●	●	–	–	●	●	●	●	●	–	●	●
Swath-laying position		left	left	left	left	left	left	left	left	left	left	left	left	left
Four-wheel rotor chassis		●	●	●	●	●	●	●	●	●	●	●	●	●
Six-wheel rotor chassis		○	○	○	–	–	–	–	○	–	–	–	–	–
<b>Tyres</b>														
Rotor chassis	16 × 6.50-8 10 PR	2 × 4 (2 × 6 ○)	●	2 × 4 (2 × 6 ○)	●	●	–	–	2 × 4 (2 × 6 ○)	4	4	4	–	–
	18 × 8.50-8 6 PR	–	–	–	–	–	2 × 4	2 × 4	–	–	–	–	4	4
Main frame	10.00/75-15.3 10 PR	–	●	2	●	●	–	–	–	–	–	–	–	–
	380/55-17	2	–	–	–	–	–	–	–	–	–	–	–	–
	340/55-16	–	○	2 (○)	○	○	–	–	–	–	–	–	–	–
Fully floating suspension		●	●	●	●	●	● <sup>5</sup>	● <sup>5</sup>	●	–	–	–	–	–
<b>Drive systems</b>														
PTO shaft speed	rpm	540	540	540	540	540	540	540	540	540	540	540	540	540
Single wide-angle PTO drive shaft		●	●	●	●	●	●	●	–	–	–	–	●	●
<b>Convenience</b>														
Spare wheel 16 × 6.50-8 10 PR		○	○	○	○	○	–	–	–	–	–	–	–	–
Spare wheel 18 × 8.50-8 6 PR		–	–	–	–	–	○	○	–	–	–	–	–	–
Wheel weights		○	○	○	○	○	–	–	–	–	–	–	–	–
Double wide-angle PTO drive shaft		–	–	–	–	–	○	○	–	–	–	–	–	–
TWIN function		–	–	●	●	–	●	●	–	–	–	–	–	–
Guide wheel at front		–	–	–	–	–	○	○	–	○	○	○	○	○
Hydraulic folding of swath guard		–	○	–	○	○	○	○	○	○	○	–	○	○
Hydraulic rotor height adjustment		○	○	–	○	○	–	–	○	○	○	–	–	–
Warning sign		–	–	–	–	–	–	–	○	○	○	○	○	○
Warning sign with illumination		●	●	●	●	●	●	●	○	○	○	○	○	○
Parallelogram drawbar		–	–	–	–	–	●	○	–	–	–	–	○	○
Hydraulic spool valves		1 × sa	1 × sa	1 × sa	1 × sa	1 × sa	1 × sa	1 × sa	–	–	–	–	1 × sa	1 × sa
		1 × da	–	1 × da	1 × da	–	1 × da	1 × da	+ 1 or 2 × da <sup>6</sup>	+ 1 or 2 × da <sup>6</sup>	+ 1 or 2 × da <sup>6</sup>	–	+ 1 × da <sup>6</sup>	+ 1 × da <sup>6</sup>

- Swath former cloth guard
- TWIN function (option) with additional swath guard for front rotor
- Swath guard and protective frame folded

- LINER 370 with single axle
- Rear only
- 1 da each for hydraulic rotor height adjustment and hydraulic swath guard folding

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed to present the function more clearly in photographs. To avoid any risks, you should never remove these protective panels yourself. In this context, please refer to the relevant instructions in the operator's manual.

● Standard ○ Option □ Available – Not available.

● Standard ○ Option □ Available – Not available.

LINER central swathers		4000	3600	3100	2900	2800	2700	2600
		Four-rotor swathers			Dual-rotor swathers			
Hitch category		Cat. III	Cat. II	Cat. II	Cat. II	Cat. II	Cat. II	Cat. II
Working width	m (DIN)	12.20–15.00	9.90–12.50	8.70–10.00	8.00–9.00	7.40–8.20	6.80–7.40	6.20–6.80
Swath width <sup>1 ca.</sup>	m	1.50–2.60	1.20–2.30	1.50–2.60	1.20–2.40	1.20–2.20	1.20–2.00	1.10–1.80
Transport width								
With tine arms mounted	m	3.00	3.00	2.97	2.97	2.97	2.97	2.97
Transport height								
With tine arms mounted	m	3.99	3.99 <sup>2</sup>	4.46	3.99	3.99	3.99	3.99
With tine arms removed	m	3.57	3.40	3.75	3.72	3.47	3.38	3.18
Parking length (transport position)	m	10.16	8.70	6.92	6.53	6.53	5.87	5.87
Rotors	Qty	4	4	2	2	2	2	2
Rotor diameter	m	3.80	3.30	4.20	3.80	3.50	3.20	2.90
Tine arms per rotor	Qty	14	12	14	14	12	12	11
Dual tines per arm set	Qty	4	4	5	4	4	4	4
Tine diameter	mm	9.5	9.5	9.5	9.5	9.5	9	9
PROFIX tine arm bracket		●	●	●	●	●	●	–
Swath-laying position		Centre	Centre	Centre	Centre	Centre	Centre	Centre
Four-wheel rotor chassis		● <sup>3</sup>	●	–	● <sup>3</sup>	● <sup>3</sup>	●	●
Six-wheel rotor chassis		○ <sup>4</sup>	–	● <sup>3</sup>	○	○	○	–
Fully floating suspension		●	●	●	●	●	●	●
<b>Drive systems</b>								
PTO shaft speed	rpm	540	540	540	540	540	540	540
Single wide-angle PTO drive shaft		●	●	●	●	●	●	●
<b>Tyres</b>								
Rotor chassis								
16 × 6.50-8 10 PR		4 × 4	4 × 4	2 × 6	2 × 4	2 × 4	2 × 4	2 × 4
Main frame								
10.00/75-15.3 10 PR		–	–	–	–	2	2	2
500/55-20		–	○	–	–	–	–	–
620/40 R 22.5		2	○	–	–	–	–	–
380 /55 - 17		–	2	2	2	○	–	–
Weight approx.	kg	5480	4600	2800	2250	2050	1900	1600
<b>Convenience</b>								
Spare wheel 16 × 6.50-8 10 PR		○	○	○	○	○	○	○
Wheel weights		–	–	●	○	○	○	–
Single-rotor lifting function (three-way valve)		–	–	○	○	○	○	○
Electrohydraulic individual rotor lift		●	●	○	○	○	–	–
Electrohydraulic rotor height adjustment		○	○	○	○	○	–	–
LED working lights		○	○	–	–	–	–	–
Hydraulic spool valves		–	1 × sa	1 × sa	1 × sa	1 × sa	1 × sa	1 × sa
		1 × sa + fR or LS	1 × sa + fR or LS	1 × da	1 × da	1 × da	–	–

1 Depending on forage conditions and engine speed

2 For tyre variant 500/55-20

3 Front lateral suspension

4 For rear pair of rotors

● Standard ○ Option □ Available – Not available.