

WOODS

FINISHING MOWERS

QUALITY MACHINES
BUILT FOR EFFICIENCY
AND DURABILITY



woodsequipment.com.au

WORKING HARD FOR GENERATIONS



FINISHING MOWERS

Table of Contents

| | |
|---|-----------|
| Time To Get Even..... | 2 |
| Finishing Mowers Features & Benefits..... | 3 |
| Standard Duty Finishing Mower Series..... | 5 |
| TK60.20W | |
| TK72.20W | |
| Specifications Table..... | 6 |
| Heavy Duty Finishing Mower Series..... | 7 |
| TKP60.40W | |
| TKP72.40W | |
| TKP84.40W | |
| Specifications Table..... | 8 |
| Extra Heavy Duty Finishing Mower Series..... | 9 |
| RD990XW | |
| Specifications Table..... | 9 |
| Standard Duty Flex Wing Finishing Mower Series | 10 |
| TBW12.20W | |
| Specifications Table..... | 10 |
| Heavy Duty Flex Wing Finishing Mower Series | 11 |
| TBW12.40W | |
| TBW15.40W | |
| TBW17.40W | |
| Specifications Table..... | 12 |
| Quick Reference Specifications Tables..... | 13 |



Since 1946 Woods have been manufacturing Woods Equipment in Oregon, Illinois. Woods are American made with American steel - quality machines built to last.

Woods in Australia

TISCA (Tractor Implement Supply Company of Australia Pty Ltd) have been importing Woods equipment for over 15 years. TISCA also manufactures side throw options for all Woods slashers in Australia.

Find a Woods Dealer

Woods Equipment is distributed through a network of authorised dealers. To find your nearest dealer visit us at woodsequipment.com.au or call (07) 5441 5677

TIME TO GET EVEN

EVEN CUT. EVEN DISTRIBUTION. EVEN COSTS LESS TO OWN.

TURFKEEPER™



TK60.20W

Driveline Holder

Keep the drive out of the dirt, even when attaching.



3-year Gearbox Warranty

Confidence in the durability of your Woods mower.



1-year Spindle Warranty

Lubed for life spindles with one year warranty provide ease of mind.

TURFKEEPER PRO™

Ease of Attachment

Quick-hitch ready from the factory for ease of attachment.

Durability

Premium, solid rubber caster wheels for performance and durability.

Tapered Roller Bearings

Tapered roller bearings in caster wheels provide superior performance and longevity in rough conditions.



TK72.40W



6-year Gearbox Warranty

With twice the oil capacity of many competitors and an improved breather system that maintains oil lubrication of gears, RD990X gearboxes carry a 6-year limited warranty to ensure years of worry-free performance.

Replaceable Side Skids

Replaceable side skids attach to heavy side frames for durability and long life.



RD990XW

So... Why Woods?

Introducing the new rear-mount finishing mowers from Woods, the TurfKeeper, designed to deliver outstanding cut quality at a lower cost of ownership. The TurfKeeper Pro, our new, premium, rear-mount finishing mowers designed with maximum durability for commercial and residential applications, and the newly redesigned TurfBatwing, our triple-deck, rear-discharge, flex wing finishing mower for large lawns and estates.



3-year Gearbox Warranty

Confidence in the durability of your Woods mower.



Automatic Belt Tensioner

No spanners or time required to maintain correct tension.



Chain Shielding

Helps prevent discharge of foreign objects.



Easy Shield Removal

No tools needed to access belt sheaves, belt, spring-loaded idler.



Cast Iron Sheaves

Better belt grip for extended belt life.



Serviceable Belt Idler

Replaceable idler post and bronze bushing.



Driveline Holder

Keep the drive out of the dirt, even when attaching.



Optional Front Roller

Anti-scalp protection for uneven terrain.



1-year Spindle Warranty

Lubed for life spindles with one year warranty provide ease of mind.



**TIME TO
GET EVEN**

**EVEN CUT.
EVEN DISTRIBUTION.
EVEN COSTS LESS TO OWN.**

**IT'S TIME TO GET EVEN
WITH YOUR GRASS
LIKE A PRO!**

20 Series

Standard Duty Finishing Mowers

The TurfKeeper Standard-Duty Finishing Mowers are designed for tractors up to 35hp PTO with a cutting width from 1.5m (5') to 1.83m (6'). The Standard-Duty finishing mower is ideal for mowing grass on a compact tractor in domestic and commercial applications.



- High-lift blades for best in class lifting and cutting of green material for evenness of cut
- Parallel frame deck sides spread material from edge to edge for even material distribution
- High blade tip speeds enhance productivity with improved mowing at higher speeds for less time on the job
- Hitch: Limited CAT 1 (TK60.20W) and CAT 1 (TK60.20W & TK72.20W)

Tractor PTO HP Range:

15 - 35hp

Models

TK60.20W | 1.5m (5')

TK72.20W | 1.83m (6')

**WORKING FOR
GENERATIONS
TO COME!**

| SPECIFICATIONS | | | 20 SERIES STANDARD DUTY FINISHING MOWERS | | |
|--------------------------------|--|--|--|--|--|
| MODEL | TK60.20W | | TK72.20W | | |
| Tractor PTO Horsepower | 15hp - 35hp | | 20hp - 35hp | | |
| Gearbox Horsepower | 35hp | | | | |
| Cutting Width | 1.5m (5') | | 1.8m (6') | | |
| Cutting Height Range | 35mm - 125mm | | | | |
| Shielding | Chain Shielding | | | | |
| Weight | 264kg | | 289kg | | |
| Transport Width | 1.55m (5.1') | | 1.85m (6.1') | | |
| Deck Thickness | 4.1mm | | | | |
| Side Skirt | 4.1mm x 117mm Deep | | | | |
| Hitch / Quick Hitch Compatible | Cat 1 / Yes | | | | |
| Tip Speed | 17,900fpm | | 18,000fpm | | |
| Blade Overlap | 38mm | | | | |
| Blade Spindles / Bearings | 3 cast iron housing / greaseable ball bearings | | | | |
| Blade Sheave | Steel | | | | |
| Blade Crossbar | - | | | | |
| Caster Wheels | 3.25 x 10 solid rubber | | | | |
| Tractor PTO Speeds | 540rpm | | | | |
| Driveline Size | Cat 3 | | | | |
| Belt | 'B' size Kevlar V-Belt with automatic belt tension | | | | |
| Belt Adjustment | Spring Loaded Idler | | | | |
| Mower Warranty | 1 year | | | | |
| Gearbox Warranty | 3 year | | | | |
| Spindle Warranty | 1 year | | | | |

40 Series

Heavy Duty Finishing Mowers

The TurfKeeper Pro Heavy-Duty Finishing Mowers are designed for tractors up to 60hp PTO with a cutting width from 1.5m (5') and 2.1m (7'). The Heavy-Duty finishing mower is ideal for commercial applications including vineyards, contractors, councils and orchards.



- Heavy duty construction provides maximum durability
- Strong, 7 gauge steel deck and a powerful 60hp gearbox
- Uniquely designed for best-in-class cut quality
- Floating lower hitch helps to follow ground contours for a smooth, even cut
- Easy cover removal - no tools needed to access belt pulleys & idlers
- Deep deck and high blade tip speeds help you get the job done faster
- Optional chain shielding attaches and detaches easily
- Ideal for mowing large lawns, sports fields and parks
- Superior baffle design distributes material more evenly

Tractor PTO HP Range:

15 - 50hp

Models

TKP60.40W | 1.5m (5')
TKP72.40W | 1.83m (6')
TKP84.40W | 2.1m (7')

**TURFKEEPER PRO DELIVERS BEST-IN-CLASS CUT QUALITY AT A LOWER COST OF OWNERSHIP.
IT'S TIME TO GET EVEN WITH YOUR GRASS
LIKE A PRO!**

| SPECIFICATIONS | | | | 40 SERIES HEAVY DUTY FINISHING MOWERS | | | |
|--------------------------------|--|--|--------------|---------------------------------------|-------------|--|--|
| MODEL | TKP60.40W | | TKP72.40W | | TKP84.40W | | |
| Tractor PTO Horsepower | 15hp - 50hp | | 20hp - 50hp | | 25hp - 50hp | | |
| Gearbox Horsepower | 60hp | | | | | | |
| Cutting Width | 1.5m (5') | | 1.8m (6') | | 2.1m (7') | | |
| Cutting Height Range | 25mm - 140mm | | | | | | |
| Shielding | Chain Shielding | | | | | | |
| Weight | 330kg | | 364kg | | 420kg | | |
| Transport Width | 1.55m (5.1') | | 1.85m (6.1') | | 2.2m (7.2') | | |
| Deck Thickness | 4.1mm | | | | | | |
| Side Skirt | 4.1mm x 136mm with 140mm diameter skid rod bumper | | | | | | |
| Hitch / Quick Hitch Compatible | Cat 1 / Yes | | | | | | |
| Tip Speed | 18,000fpm | | 18,100fpm | | 18,100fpm | | |
| Blade Overlap | 38mm | | | | | | |
| Blade Spindles / Bearings | 3 cast iron housing / greaseable ball bearings | | | | | | |
| Blade Sheave | Cast iron with taper lock bushing | | | | | | |
| Blade Crossbar | Yes | | | | | | |
| Caster Wheels | 100mm x 250mm | | | | | | |
| Tractor PTO Speeds | 540rpm | | | | | | |
| Driveline Size | Cat 3 | | | | | | |
| Belt | 'B' size Kevlar V-Belt with automatic belt tension | | | | | | |
| Belt Adjustment | Spring Loaded Idler | | | | | | |
| Mower Warranty | 1 year | | | | | | |
| Gearbox Warranty | 6 year Limited | | | | | | |
| Spindle Warranty | 3 year Limited | | | | | | |

RD990XW

Extra Heavy Duty Finishing Mower

The Woods Equipment RD990XW Finishing Mower is an Extra Heavy-Duty mower with a 2.3m (8') cutting width and a 75hp gearbox, designed and manufactured for extreme usage and the most demanding applications. The Woods RD990X rear discharge finishing mower is tough yet versatile enough to move from rough, weedy farmland to commercial lawns and landscape applications.



Tractor PTO HP Range:
45 - 75hp

- Three - point hitch: CAT 1 and 2.
- Takes down grass and light weeds, and leaves a high grade finish cut behind.
- Features a patented Quick-change blade system, an extra strong double B - section belt, and anti - wrap bars that prevent damage caused by material wrapped around lower spindle.
- Deep deck and stump jumper blade carrier with free-swinging blades ideal for rough grass.
- Floating lower hitch points allow the mower to follow uneven terrain.
- Chain shielding standard.

| SPECIFICATIONS | EXTRA HEAVY DUTY FINISHING MOWER |
|---|--|
| MODEL | RD990XW |
| Tractor PTO Horsepower | 45hp - 75hp |
| Gearbox Horsepower | 75hp |
| Cutting Width | 2.3m (8') |
| Cutting Height Range | 38mm |
| Weight | 605kg |
| Transport Width | 2.46m |
| Deck Material Thickness | 7 Gauge |
| Side Skirt | 8mm Thick x 18.25mm |
| Blade Tip Speed | 17,000fpm |
| Blade Overlap | 50mm |
| Blade Spindles / Bearings | 3 cast iron housing / greaseable ball bearings |
| Blade Sheave | Cast iron with taper lock bushing |
| Blade Crossbar | Yes, Free Swinging Blades |
| Caster Wheels | 125mm x 330mm |
| Tractor PTO Speed | 540rpm |
| Driveline Size | Cat 4 |
| Hitch / Quick Hitch Compatible | Cat 1 & 2 / Yes |
| Belt / Belt Adjustment | Powerband with double B - Section Kevlar / Spring Loaded Idler |
| Front Centre Roller / Front Anti-Scalp Roller | Optional |
| Shielding | Chain Shielding |
| Mulching Kit | - |
| Mower Warranty | 1 year |
| Gearbox Warranty | 6 year Limited |
| Spindle Warranty | 3 year Limited |

Wide Area Estate TurfBatwing

Standard Duty Flex Wing Finishing Mower

The Woods Standard-Duty TurfBatwing TBW12.20W is a triple-deck, rear-discharge, flexing finishing mower for large lawns and estates. The Woods Standard-Duty TurfBatwing TBW12.20W suits tractor with up to 60hp tractor PTO horsepower.



Tractor PTO HP Range:

25 - 60hp

Models

TBW12.20W | 3.8m (12.5')

- High-lift blades for best-in-class lifting and cutting of green material for evenness of cut.
- Parallel deck side frames spread material from edge to edge for even material distribution.
- High blade tip speeds enhance productivity with improved mowing at higher speeds for less time on the job.
- Trust the Woods legacy for durable, high-quality cutting equipment for all your mowing needs.

| SPECIFICATIONS | WIDE AREA ESTATE TURFBATWING |
|----------------------------------|--|
| MODEL | TBW12.20W |
| Tractor PTO Horsepower | 25hp - 60hp |
| Gearbox Horsepower | 100hp Splitter / 35hp Mower Deck |
| Cutting Width | 3.8m (12.5') |
| Cutting Height Range | 25mm - 115mm |
| Cutting Height Adjustment | Spacer on caster |
| Shielding | Chain Shielding |
| Weight | 968kg |
| Wing Deck Cutting Width | 1.37m (4.5') |
| Deck Overlap | 15cm (5.9") |
| Deck Thickness | 3.2mm steel plate |
| Overall Width | 3.83m (12.5') |
| Transport Width | 2.36m (7.7') |
| Maximum Overall Length | 3.43m (12.5') |
| Transport Length | 3.2m (10.5') |
| Hitch | Floating Clevis, Multi-Position |
| Angle Operating Range | 20° up / 15° down |
| Blade Tip Speed | 16,200fpm |
| Blade Spindle Bearings | Greaseable ball bearings |
| Blade Dimensions | 6mm x 63.5mm (0.25" x 2.5") |
| Blade Spindles | Cast Iron |
| Drive Type | Gearbox over V-Belt |
| Input Driveline / Wing Driveline | Cat 3 CV (Constant Velocity) / Cat 3 |
| Tyres | 20.5 x 9 non-highway speed rated transport tyres |
| Caster Wheels | 10 x 4 solid rubber gauge wheels |
| Caster Wheel Bearings | Power metal bushing |
| Wing Deck Lift Cylinders | 7.6cm x 25.4cm (3" x 10") Single Acting |
| Centre Deck Lift Cylinders | 8.9cm x 20.3cm (3" x 8") Single Acting |
| Trailer Frame Construction | 6mm (0.25") Wall Tubing |
| Belts | B - Section Kevlar |
| Belt Adjustment | Spring-loaded idler |
| Mower Warranty | 1 year |
| Gearbox Warranty | 3 year Limited |
| Spindle Warranty | 1 year |

Commercial TurfBatwing

Heavy Duty Flex Wing Finishing Mower

The Woods Commercial Turf Batwing Finishing Mower is a Heavy-Duty model of the Woods TurfBatwing Finishing Mower range. With cutting widths from 3.6m (12') to 5.1m (17'), the Commercial TurfBatwing Finishing Mowers are designed for tractors with a PTO hp range from 35hp - 100hp.



- Angle operating range 25° up and 22° down
- 25mm - 125mm cutting height range
- Blade tip speed of 18,000fpm
- 10 large caster wheels provide even cut on rough ground
- Decks are designed with "box" construction which adds structural depth
- Three decks mounted to heavy-duty trailer for triple cut capacity
- Folded transport width of 2.44m
- 6 year limited gearbox warranty, 3 year limited spindle warranty

Tractor PTO HP Range:
35 - 100hp

Models

TBW12.40W | 3.6m (12')
TBW15.40W | 4.5m (15')
TBW17.40W | 5.1m (17')

**WOODS COMMERCIAL TURF BATWING
FINISHING MOWERS ARE DESIGNED FOR
OUTSTANDING CUT QUALITY AND BUILT
FOR A LONG, DURABLE LIFE.**

Commercial Rear Discharge TurfBatwing

| SPECIFICATIONS | | | | COMMERCIAL REAR DISCHARGE TURFBATWING | | | |
|----------------------------------|---|--|-----------------------------------|---------------------------------------|---------------|--|--|
| MODEL | TBW12.40W | | TBW15.40W | | TBW17.40W | | |
| Tractor PTO Horsepower | 35hp - 90hp | | 40hp - 100hp | | 50hp - 100hp | | |
| Gearbox Horsepower | 100hp Splitter / 75hp Mower Deck | | | | | | |
| Cutting Width | 3.6m (12') | | 4.5m (15') | | 5.1m (17') | | |
| Cutting Height Range | 25mm - 125mm | | | | | | |
| Cutting Height Adjustment | Spacer on caster | | | | | | |
| Shielding | Chain Shielding | | | | | | |
| Weight | 1,361kg | | 1,508kg | | 1,588kg | | |
| Wing Deck Cutting Width | 1.23m (4') | | 1.52m (5') | | 1.83m (6') | | |
| Deck Overlap | 16.5cm (6.5") | | 15cm (5.9") | | | | |
| Deck Thickness | 4.1mm | | | | | | |
| Overall Width | 3.71m (12.2') | | 4.62m (15.1') | | 5.23m (17.1') | | |
| Transport Width | | | 2.54m (8.3') | | 2.9m (9.5') | | |
| Maximum Overall Length | 4.39m (14.4') | | 4.65m (15.2') | | | | |
| Transport Length | 4.01m (13.1') | | 4.09m (13.4') | | | | |
| Hitch | Floating Clevis, Multi-Position | | | | | | |
| Angle Operating Range | 25° up / 22° down | | | | | | |
| Blade Tip Speed | 18,000fpm | | | | | | |
| Blade Spindle Bearings | Greaseable tapered roller | | | | | | |
| Blade Dimensions | 6mm x 63.5mm (0.25" x 2.5") | | | | | | |
| Blade Spindles | Cast Iron | | | | | | |
| Drive Type | Gearbox over V-Belt | | | | | | |
| Input Driveline / Wing Driveline | Cat 4 CV (Constant Velocity) / Cat 3 | | | | | | |
| Tyres | 20.5 x 8 load range "D" highway service transport tyres | | | | | | |
| Caster Wheels | 15 x 6-6 pneumatic gauge wheels | | 18 x 9.5-8 pneumatic gauge wheels | | | | |
| Caster Wheel Bearings | Tapered roller bearings | | | | | | |
| Wing Deck Lift Cylinders | 8.9cm x 25.4cm (3.5" x 10") Single Acting | | | | | | |
| Centre Deck Lift Cylinders | 8.9cm x 20.3cm (3" x 8") Single Acting | | | | | | |
| Trailer Frame Construction | 6mm (0.25") Wall Tubing | | | | | | |
| Belts | B - Section Kevlar | | | | | | |
| Belt Adjustment | Spring-loaded idler | | | | | | |
| Mower Warranty | - | | | | | | |
| Gearbox Warranty | 6 year Limited | | | | | | |
| Spindle Warranty | 3 year Limited | | | | | | |

| SPECIFICATIONS | | FINISHING MOWER SERIES | | | | |
|--------------------------------|--|------------------------|---|--------------|-------------|--|
| MODEL | TK60.20W | TK72.20W | TKP60.40W | TKP72.40W | TKP84.40W | RD990XW |
| Tractor PTO Horsepower | 15hp - 35hp | 20hp - 35hp | 15hp - 50hp | 20hp - 50hp | 25hp - 50hp | 45hp - 75hp |
| Gearbox Horsepower | 35hp | | 60hp | | | 75hp |
| Cutting Width | 1.5m (5') | 1.8m (6') | 1.5m (5') | 1.8m (6') | 2.1m (7') | 2.3m (7.5') |
| Cutting Height Range | 35mm - 125mm | | 35mm - 120mm | | | 38mm |
| Shielding | Chain Shielding | | | | | |
| Weight | 264kg | 289kg | 330kg | 364kg | 420kg | 605kg |
| Transport Width | 1.55m (5.1') | 1.85m (6.1') | 1.55m (5.1') | 1.85m (6.1') | 2.2m (7.2') | 2.46 (8.1') |
| Deck Thickness | 4.1mm | | | | | 4.5mm |
| Side Skirt | 4.1mm x 117mm Deep | | 4.1mm x 136mm with 140mm diameter skid rod bumper | | | 8mm thick x 18.25mm |
| Hitch / Quick Hitch Compatible | Cat 1 / Yes | | | | | Cat 1 & 2 / Yes |
| Tip Speed | 17,900fpm | 18,000fpm | 18,000fpm | 18,100fpm | 18,100fpm | 17,000fpm |
| Blade Overlap | 38mm | | | | | 50mm |
| Blade Spindles / Bearings | 3 cast iron housing / greaseable ball bearings | | | | | |
| Blade Sheave | Steel | | Cast iron with taper lock bushing | | | |
| Blade Crossbar | - | | Yes | | | Yes, Free Swinging Blades |
| Caster Wheels | 3.25 x 10 solid rubber | | 100mm x 250mm | | | 125mm x 330mm |
| Tractor PTO Speeds | 540rpm | | | | | |
| Driveline Size | Cat 3 | | | | | Cat 4 |
| Belt | 'B' size Kevlar V-Belt with automatic belt tension | | | | | 'B' size Kevlar V-Belt with automatic tension adjustment |
| Belt Adjustment | Spring Loaded Idler | | | | | |
| Mower Warranty | 1 year | | | | | |
| Gearbox Warranty | 3 year | | 6 year Limited | | | |
| Spindle Warranty | 1 year | | 3 year Limited | | | |
| Options | | | | | | Front Centre Roller / Front Anti-Scalp Roller |

| SPECIFICATIONS | | | | |
|---|--|---|-----------------------------------|------------------|
| TURFBATWING FINISHING MOWER SERIES | | | | |
| MODEL | TBW12.20W | TBW12.40W | TBW15.40W | TBW17.40W |
| Tractor PTO Horsepower | 25hp - 60hp | 35hp - 90hp | 40hp - 100hp | 50hp - 100hp |
| Gearbox Horsepower | 100hp Splitter / 35hp Mower Deck | 100hp Splitter / 75hp Mower Deck | | |
| Cutting Width | 3.8m (12.5') | 3.6m (12') | 4.5m (15') | 5.1m (17') |
| Cutting Height Range | 25mm - 115mm | 25mm - 125mm | | |
| Cutting Height Adjustment | Spacer on caster | | | |
| Shielding | Chain Shielding | | | |
| Weight | 968kg | 1,361kg | 1,508kg | 1,588kg |
| Wing Deck Cutting Width | 1.37m (4.5') | 1.23m (4') | 1.52m (5') | 1.83m (6') |
| Deck Overlap | 15cm (5.9") | 16.5cm (6.5") | 15cm (5.9") | |
| Deck Thickness | 3.2mm steel plate | 4.1mm | | |
| Overall Width | 3.83m (12.5') | 3.71m (12.2') | 4.62m (15.1') | 5.23m (17.1') |
| Transport Width | 2.36m (7.7') | | 2.54m (8.3') | 2.9m (9.5') |
| Maximum Overall Length | 3.43m (12.5') | 4.39m (14.4') | 4.65m (15.2') | |
| Transport Length | 3.2m (10.5') | 4.01m (13.1') | 4.09m (13.4') | |
| Hitch | Floating Clevis, Multi-Position | | | |
| Angle Operating Range | 20° up / 15° down | 25° up / 22° down | | |
| Blade Tip Speed | 16,200fpm | 18,000fpm | | |
| Blade Spindle Bearings | Greaseable ball bearings | Greaseable tapered roller | | |
| Blade Dimensions | 6mm x 63.5mm (0.25" x 2.5") | | | |
| Blade Spindles | Cast Iron | | | |
| Drive Type | Gearbox over V-Belt | | | |
| Input Driveline / Wing Driveline | Cat 3 CV (Constant Velocity) / Cat 3 | Cat 4 CV (Constant Velocity) / Cat 3 | | |
| Tyres | 20.5 x 9 non-highway speed rated transport tyres | 20.5 x 8 load range "D" highway service transport tyres | | |
| Caster Wheels | 10 x 4 solid rubber gauge wheels | 15 x 6-6 pneumatic gauge wheels | 18 x 9.5-8 pneumatic gauge wheels | |
| Caster Wheel Bearings | Power metal bushing | Tapered roller bearings | | |
| Wing Deck Lift Cylinders | 7.6cm x 25.4cm (3" x 10") Single Acting | 8.9cm x 25.4cm (3.5" x 10") Single Acting | | |
| Centre Deck Lift Cylinders | 8.9cm x 20.3cm (3" x 8") Single Acting | | | |
| Trailer Frame Construction | 6mm (0.25") Wall Tubing | | | |
| Belts | B - Section Kevlar | | | |
| Belt Adjustment | Spring-loaded idler | | | |
| Mower Warranty | 1 year | - | | |
| Gearbox Warranty | 3 year Limited | 6 year Limited | | |
| Spindle Warranty | 1 year | 3 year Limited | | |



1137 Nambour Connection Rd, Parklands QLD 4560

(07) 5441 5677

woodsequipment.com.au
tisca.com.au

WOODS

Warning! Some images may show safety shields removed to provide a better view. Equipment should never be operated with any safety shield removed. Some machines in this brochure may be shown with optional equipment. Always operate machines in accordance with supplied operator's manuals. ©2021 Woods Equipment Company. All rights reserved. WOODS and Woods logo are trademarks of Woods Equipment Company. All other trademarks, trade names, or service marks not owned by Woods Equipment Company that appear in this brochure are the property of their respective companies or mark holders. Specifications subject to change without notice.