



## WORKING FOR GENERATIONS TO COME!

Grading dirt or driveways, cleaning up construction sites or moving snow – rely on Woods durable Rear Blades for maximum performance.

Ranging from standard duty to heavy duty grader blades, Woods have a rear grader blade to suit all applications including having a range to suit compact and sub compact tractors. All tilt models of the Woods rear grader blades have a rotation of 360°. The reversible cutting edge provides a long service life. Cutting width ranges from 1.3m (4.6ft) to 2.4m (8ft). Optional rear wheel available.

- Formed moldboard made from high-strength steel provides exceptional rigidity and pivots 360°
- Double-bevelled, reversible, bolt-on cutting edge adds to product life and enables easy replacement



Tractor PTO HP Range:

**up to 30HP**

Basic Models

**RBS54** | up to 30hp

**RBS60** | up to 30hp

**RBS72** | up to 30hp



Tractor PTO HP Range:

**20 - 45HP**

Premium Models

**RBS60P** | 20 - 45hp

**RBS72P** | 20 - 45hp



Tractor PTO HP Range:

**30 - 75HP**

Medium-duty 50 Series

**RB72.50** | 30 - 65hp

**RB96.50** | 30 - 75hp



Tractor PTO HP Range:

**40 - 100HP**

Medium-duty 60 Series

**RB96.60** | 40 - 100hp



Tractor PTO HP Range:

**50 - 180HP**

Heavy-duty Models

**RB850** | 50 - 120hp

**RB1010** | 80 - 180hp

## WOODS POWER - POWER TO BE MORE PRODUCTIVE



**RB72.50**

SPECIFICATIONS		REAR BLADES								
MODEL	RBS54	RBS60	RBS72	RBS60P	RBS72P	RB72.50	RB96.50	RB96.60	RB850	RB1010
Tractor PTO Horsepower	up to 30hp			20 - 45hp		30 - 65hp	30 - 75hp	40 - 100hp	50 - 120hp	80 - 180hp
Tractor Hitch	Cat 1 & Limited Cat 1 (sub compact)			Cat 1		Cat 1 & Cat 2			Cat 2	Cat 2 & Cat 3
Working Width	1.35m (53")	1.5m (59")	1.8m (71")	1.5m (59")	1.8m (71")	1.8m (71")	2.4m (95")			3m (119")
Moldboard Height	30cm			38cm		43cm	44cm	43cm	46cm	
Moldboard Thickness	4.62mm (0.182") grade 80 Steel			3.17mm (0.125") grade 80 steel		6.35mm (0.25") grade 80 steel	7.95mm (0.313") grade 80 steel	7.95mm (0.313")	6.35mm (0.25")	
Weight	60kg	64kg	70kg	121kg	130kg	206kg	224kg	330kg	560kg	696kg
Double-Bevelled, Reversible Cutting Edge Dimensions	9.5mm x 152mm (0.375" x 6")			12.7mm x 152mm (0.5" x 6")						
Angle Adjustments	5 Positions up to 30°					7 positions up to 45° (m or h)	up to 45° (m or h)	9 forward up to 60°; 5 reverse up to 30° (m or h)	up to 60° (h)	
Offset Adjustments	-			up to 30cm (12") left or right	15cm, 30cm, 45cm (6", 12", 18") left or right	up to 50cm (m or h)	up to 60cm (m or h)	up to 84cm (m or h)		
Tilt Adjustments	-			up to 15°	5 positions up to 23°	up to 23° (m or h)	up to 30° (m or h)	up to 28° (m or h)		
End Plates	-			Optional						-
Skid Shoes	Optional									-
Tailwheel	-						Optional			
Parking Stand	Optional					Standard				
ASABE Quick-Hitch Compatible						Yes				

M = Manual - H = Hydraulic