



WORKING FOR GENERATIONS TO COME!

What's your soil type? Are you cutting into an established lawn or simply turning over the ground after harvest?

Woods tillage equipment has innovative design features that make them easy to use, durable and highly productive.

In fact, the double flange blade support design and efficient, low-maintenance gear drive are just two innovations that earned our 30- and 40-series rotary tillers the 2017 ASABE Award for outstanding innovations in product and systems technology.



Strong Blade Support

Woods' innovative double flange design strengthens blade support and simplifies maintenance.

Gear-driven Side Drive

Robust gear-driven side drive provides years of reliable service and requires far less maintenance than chain-driven units.



3-year Gearbox Warranty

Woods 3-year input gearbox warranty includes seals.



High-strength Steel

Heat-treated, C-shaped tines penetrate deep, even in thick residue and loose, compacted or rocky soil.

Fixed Offset

Fixed offset tiller width covers tire tracks with each pass.

Easy Depth Control

Adjustable skid shoes provide easy depth control.

Easy Hook-up

Sturdy tubular integrated parking stand ensures easy storage and hook-up.

Finished Seedbed

Tapered tailgate removes furrow for a finished seedbed.

**WOODS' LINE OF ROTARY TILLERS
COUPLES THE BEST DESIGN FEATURES
WITH OUTSTANDING PERFORMANCE!
OUR TILLERS WILL HANDLE YOUR
LANDSCAPING AND GARDENING
PROJECTS WITH EASE.**

WORKING FOR GENERATIONS TO COME!



Woods offers tillers in forward or reverse rotation in 41" – 74" widths.

When you're ready to dig in and work the soil, turn to Woods. We bring a well-earned reputation for durability, reliability and innovation to our line of tillage equipment. Woods rotary tillers and disc harrows are designed for a wide range of projects on homes, small farms, orchards or nurseries, and for anyone living the country life. Choose from a large selection of widths, depending upon your tasks.

Forward rotation tillers

Ideal for moist, wet, rocky, sandy or loose soil conditions.

Reverse rotation tillers

Works best in non-rocky soil conditions. They deliver a smoother top layer of soil by allowing ground cover to travel over the rotor top first, then incorporating it back into the ground beneath a fresh new layer of dirt. More often than not, users can achieve an exceptional seed bed with fewer passes when using a reverse rotation tiller.



SPECIFICATIONS

ROTARY TILLER SERIES

MODEL	TC60 / TCR60	TC68 / TCR68
Tractor PTO Horsepower	20hp - 45hp	
Tractor PTO Speed	540rpm	
Tractor Hitch	Limited Cat 1 & 2	
Working Width	1.5m (5')	1.7m (5.6')
Overall Width	1.7m (5.5')	1.9m (6.2')
Weight	273kg	290kg
Maximum Tilling Depth	19cm (7.5")	
Drive Type	Chain	
Total Number of Tines / Flanges	42 / 7	48 / 8
Number of Tines per Flange	6 C-type	
Rotor Speed	240rpm	
PTO Driveline Protection	Slip clutch	
Gearbox Housing	Heavy duty cast iron	
Gearbox Drain Plug	Yes	
Offset (Left)	Adjustable up to 39cm (15.3")	Adjustable up to 49cm (19.3")
ASABE Quick-Hitch Compatible	Yes	