



*It dominates the hillside, soars over the plain*

**T** *SERIES*  
**MAJOR**



# T MAJOR Series



## TOTALLY AC TRACTORS

Dynamism, agility, efficiency are the results of these new generation, compact tractors designed for specialised agricultural operators on plains, hillsides and mountainsides along with the crops on the Mediterranean basin where grip, handling and dimensions are deciding factors. The "T" Major Series is made up of various steering or articulated models; with equal-sized wheels or with larger rear wheels. Its perfect weight distribution, guaranteed by the ACTIO™, over all four wheels, ensures grip, stability and top level safety.

### T MAJOR Series



## TN



**ACTIO**

**4 YEARS TILL YEARS EXG** Maximum Protection Guarantee

**12+12 SYNCHRONIZED WITH INVERTER**

**KM/H 30**

**KG 2200**

Wheels	Front/Rear	X	Y
7.50-16	270	1235	
8.25-16	270	1265	
7.50-18	300	1280	
250/80-18	290	1305	
280/70-18	280	1380	
300/80-15.3	285	1395	
29x12.50-15	225	1440	
31x15.50-15	240	1615	

### Model TN 5800

Chassis	ACTIO™-Full chassis with oscillation • Steering wheels • Front and rear final drive
<b>4 equal wheel drive</b>	<b>4 unequal wheel drive</b>
<b>Engine Type</b>	Direct injection • Counter rotating
Emissions Regulations	Stage 3A
N° Cylinders	4
Displacement (CC)	2188
Power kW/HP (97/68/CE)	36,5/49,7
Maximum engine revs	3000
Torque max (Nm/revs)	139/1800
Cooling	Water
Tank Capacity (litres)	42
<b>Transmission</b>	Synchronized 24 speed gear box: 12 forward and 12 reverse with inverter
<b>PTO</b>	Independent, with mechanic control, standard speed 540 rpm and synchronized
<b>Rear hydraulic lift</b>	3-points hitch Cat. 1 - Capacity (Kg): 2200
Operating Pressure (bar)	130
<b>Steering</b>	Hydraulic with 2 double acting pistons with "Load Sensing" system
<b>Brakes</b>	Mechanic rear oil bath disc brakes - Steering brakes Rear axle and parking handbrake with control lever operating the main device
<b>Weight (Kg)</b>	1630
<b>Standard Features</b>	• Front and rear differential locks, foot lock, with mechanic control • Adjustable suspension seat • Safety belts • Rear adjustable height tow hitch • Front tow hitch • Foldable protection roll bar • Adjustable wheel rims • Horn • Lights, braking and turning indicators • Unipolar socket and 7 way trailer socket • Series of control lights • Tachometer/revolution counter • Safety starting switch • Battery isolation switch
<b>Optional Features</b>	• Hydraulic power lift with draft and position control • PTO at 540 and 1000 rpm • Rear revolving working light • 4 types of ancillary hydraulic systems with single-acting and double-acting manifolds (up to 5 rear quick couplers) • Steering column adjustable in tilt • Digital speedometer • Pneumatic suspension seat • Wheel ballasts • Cast iron wheel flanges for 20" rear wheels (only for TC F)

**DIMENSIONS: TN**

**DIMENSIONS: TC F**



Wheels	Front	Rear	X	Y
8.25-16	280/85 R20	263	1325	
300/80-15.3	360/70 R20	304	1465	
280/70-18	360/70 R20	272	1435	

**4 YEARS TILL YEARS EXG** Maximum Protection Guarantee

**12+12 SYNCHRONIZED WITH INVERTER**

**KM/H 30**

**KG 2200**

### T MAJOR Series



**DIMENSIONS: SN V**

Wheels	Front/Rear	X	Y
7.50-16	270	1035	
7.50-18	300	985	
250/80-18	290	1075	
280/70-18	280	1175	
300/80-15.3	310	1180	

### Model SN 5800 V

Chassis	ACTIO™ Full chassis with oscillation • Articulated • 4 equal wheel drive • Front and rear final drive
<b>Engine Type</b>	Direct injection • Counter rotating
Emissions Regulations	Stage 3A
N° Cylinders	4
Displacement (CC)	2188
Power kW/HP (97/68/CE)	36,5/49,7
Maximum engine revs	3000
Torque max (Nm/revs)	139/1800
Cooling	Water
Tank Capacity (litres)	42
<b>Transmission</b>	Synchr. 24 speed gear box: 12 forward and 12 reverse with inverter
<b>PTO</b>	Independent, with mechanic control, standard speed 540 rpm and synchronized
<b>Rear hydraulic lift</b>	3-points hitch Cat. 1 - Capacity (Kg): 1700
Operating Pressure (bar)	130
<b>Steering</b>	Hydraulic with 2 pistons with "Load Sensing" system
<b>Brakes</b>	Hydraulic rear oil bath disc brakes - Independent emergency and parking brake: band type on transmission
<b>Weight (Kg)</b>	1600
<b>Standard Features</b>	• Front differential lock with mechanic control, rear with hydraulic control • Adjustable suspension seat • Safety belts • Rear adjustable height tow hitch • Front tow hitch • Foldable protection roll bar • Adjustable wheel rims • Horn • Lights, braking and turning indicators • Unipolar socket and 7 way trailer socket • Series of control lights • Tachometer/revolution counter • Safety starting switch • Battery isolation switch
<b>Optional Features</b>	• Hydraulic power lift with draft and position control • PTO at 540 and 1000 rpm • Rear revolving working light • 4 types of ancillary hydraulic systems with single-acting and double-acting manifolds (up to 5 rear quick couplers) • Steering column adjustable in tilt • Digital speedometer • Pneumatic suspension seat • Wheel ballasts • Lifting arms with quick release couplings • Spacers for rear and front mudguards

**4 YEARS TILL YEARS EXG** Maximum Protection Guarantee

**12+12 SYNCHRONIZED WITH INVERTER**

**KM/H 30**

**KG 1700**

## TIGRECAR



### Model TIGRECAR 5800

Chassis	ACTIO™-Full chassis with oscillation • Steering wheels • 4 equal wheel drive • Front and rear final drive
<b>Engine Type</b>	Direct injection counter rotating weight system
Emissions Regulations:	Stage 3A
N° Cylinders:	4
Displacement (CC):	2188
Power kW/HP (97/68/CE):	36,5/49,7
Maximum engine revs:	3000
Torque max (Nm/revs):	139/1800
Cooling:	Water
Tank Capacity (litres):	48,5
<b>Transmission</b>	Synchr. 16 speed gear box: 8 forward and 8 reverse with inverter
<b>PTO</b>	Standard speed 540 rpm and synchronised
<b>Steering</b>	Single double rod hydraulic cylinder
<b>Brakes</b>	Standard: Hydraulic front and rear brakes in oil bath Emergency and parking: band type on transmission
<b>Platform</b>	Suspended on Silent Block
<b>Weight (Kg)</b>	2190
<b>Tyres</b>	10.0/75-15.3 280/70 R16
<b>Standard Features</b>	• Container cm 240x150x30 complete with inclination system • Rear differential lock with hydraulic control • Hydraulic controlled drive disengagement • Adjustable sprung seat • Safety belts • Rear adjustable height tow hitch • Protection frame with 4 uprights with roof • Hydraulic system consisting of 1 simple acting distributor for movement of container • Horn • Lighting equipment • Electric power socket and plug • Stop lights and turn signals • Centralized control board • Safety starting switch on inverter and PTO • Tachometer • Battery isolation switch
<b>Optional Features</b>	• Heating cab • Windscreen with windscreen wiper • "Superbrake" system • Column adjustable in height and tilt • Flashing light

**DIMENSIONS: TIGRECAR**

**2 YEARS TILL YEARS GUARANTEE**

**8+8 SYNCHRONIZED WITH INVERTER**

**KM/H 35**

The description and illustrations in this brochure are provided simply for information purposes; they are not binding and may be varied at any time without notice.