





The Digga Vibratory Roller is available with a smooth drum, providing our customers with a productive and cost effective compaction attachment. It's versatility makes the roller highly effective on a wide range of materials including sand, gravel, soils and asphalt.

## FEATURES

- DELIVERS UP TO 3500KG OF DYNAMIC FORCE WHEN OPERATING AT 95 LPM FNSURING EVEN COMPACTION
- STEEL DRUM HAS ADJUSTABLE STEEL SCRAPER BLADES BETWEEN FRAME AND DRUM ENSURING A SMOOTH COMPACTED SURFACE
- HYDRAULIC DRIVES FOR THIS ROLLER IS FULLY ISOLATED AND PROTECTED TO PROVIDE MAXIMUM PERFORMANCE AND RELIABILITY

## Ideal Use:

These high production rollers are ideal for rental fleets, contractors, landscaping, roadways, walkways, bike paths, golf courses, bridges and parking lots.

## **Machine Suitability:**

Skid Steer Loaders





	VR-000001	VR-000003	VR-000005
Operation weight:	975 kg	946 kg	1147 kg
Dynamic force	3500 kg	3538 kg	4250 kg
Vibrating speed	2600 vpm	2600 vpm	2600 vpm
Drum Type	Smooth	Padded	Smooth
Drum width (A)	1675 mm	1675 mm	2133 mm
Drum diameter (B)	600 mm	508 mm	600 mm
Max flow	95 lpm	95 lpm	95 lpm



